

ETEL



ETEL Blanc 01



ETEL Mastic 48



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected



ETEL Lin 11

Delicate sheer curtains with a linen appearance.

Technical properties



Flame retardant



Sheer

Applications Roman blinds - Panel curtains - Curtains

Composition 100% FR polyester

Weight 105 g/m² 305 g/m² Width 290 cm

Fabric direction Room High Direction Fitting ↔ cm ↓ cm

Maintenance advice    

Labels France Terre Textile (R016)

Certifications OEKO-TEX STANDARD 100 (CQ 1006/1)

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno	
Optical index	Light reflexion :	26 %
	Light absorption :	26 %
	Light transmission :	48 %
Transparent veil	Yes	
Thermal index	Solar reflexion :	32 %
	Solar absorption :	14 %
	Solar transmission :	54 %
	UV transmission :	46 %
	Gtot :	Gt 48 % Fc 81 %
Resilience	Lightfastness (units Class/8)	6
	Dimensional Stability (%)	
	Warp	-0,5
	Weft	0
	Breaking Elongation	
	Warp	19
	Weft	24
	Breaking load (daN)	
	Warp	61
	Weft	51



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected