



OPALE 2




OPALE 2 Océan 91



OPALE 2 Tomette 60




OPALE 2 Souris 40




OPALE 2 Nacre 04




OPALE 2 Crème 02




OPALE 2 Sable 67




OPALE 2 Beige 63




OPALE 2 Brun 23




OPALE 2 Mastic 48




OPALE 2 Moka 12




OPALE 2 Marine 25




OPALE 2 Paille 06




OPALE 2 Titanium 98



OPALE 2 Noir 36




OPALE 2 emeraude 88



OPALE 2 taupe 95



OPALE 2 absinthe 132



OPALE 2 lin 11



OPALE 2 Poterie 167



OPALE 2 Moutarde 21




(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected

OPALE 2




OPALE 2 Olive 61



OPALE 2 Billard 86




OPALE 2 Peau 201



OPALE 2 Pêche 52



OPALE 2 Etang 165




OPALE 2 Glacier 43



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected



OPALE 2 Anthracite 38

This plain fabric blocks out light very effectively and is available in a wide variety of colours.

Technical properties



Flame retardant

Applications Roman blinds - Roller blinds - Panel curtains - Curtains


Composition 100% polyester with white flocked acrylic backing

Weight 290 g/m² 406 g/m² **Width** 140 cm

Fabric direction Standard Direction **Fitting** ↔ cm ↓ cm

Maintenance advice ✂ ✂ 🧼 ©

Minimum order 1 linear(s) meter(s)



Technical characteristics

Flame retardant	M1 / IMO PASS
Optical index	Light reflexion : 72 %
	Light absorption : 28 %
	Light transmission : 0 %
Thermal index	Solar reflexion : 65 %
	Solar absorption : 35 %
	Solar transmission : 0 %
	UV transmission : 0 %
	Gtot : Gt 35 % Fc 60 %
Resilience	Lightfastness (units Class/8) 5
	Breaking Elongation
	Warp 35
	Weft 11



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected