


# SIENTO WOODY



SIENTO WOODY Osier  
171




SIENTO WOODY Poivre  
181



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

*Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected*



# SIENTO WOODY Ivoire 115

Heavy chenille canvas, Siento Woody is woven with mixed dyed yarns which gives this textured chiné effect. The chenille weft gives a very pleasant and soft sense of touch. The proportion of recycled material and the manufacturing process of the yarn used to weave this quality can cause slight color variations between different batches of fabric.

## Technical properties



Flame retardant



Recycled fabrics

**Applications** Roman blinds - Panel curtains - Curtains - Decorative frames

**Composition** 100% FR polyester including 90% recycled material

**Weight** 350 g/m<sup>2</sup> **Width** 280 cm

**Fabric direction** Room High Direction **Fitting** ↔ cm ↓ cm

**Maintenance advice**     

**Labels** France Terre Textile (R016)

**Certifications** OEKO-TEX STANDARD 100 Recyclé (CQ 1006/2)

**Minimum order** 1 linear(s) meter(s)

## Technical characteristics

Flame retardant	M1	
Acoustic	Noise reduction coefficient (NRC) :	<b>0.74</b>
	Weighted sound absorption coefficient (a <sub>w</sub> ) :	<b>0.65</b>
	Acoustic absorption class (a <sub>w</sub> ) :	<b>C</b>
Resilience	Lightfastness (units Class/8)	<b>6</b>
	Pilling	<b>2</b>
	Dimensional Stability (%)	
	Warp	<b>-0.5</b>
	Weft	<b>-1</b>
	Martindale (Cycles)	<b>12000</b>
	Breaking Elongation	
	Warp	<b>48</b>
	Weft	<b>24</b>
	Breaking load (daN)	
Warp	<b>180</b>	
Weft	<b>52</b>	



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected