



VESSO




VESSO Lie de vin 202



VESSO Navy 09



VESSO Acier 18





VESSO Noir 10



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected



VESSO Rubis 59

Heavy flame-retardant velvet

Technical properties



Flame retardant

Applications Curtains - Decorative frames

Composition 100% polyester flame retardant

Weight 500 g/m² Width 140 cm

Fabric direction Standard Direction Fitting ↔ cm ↓ cm

Maintenance advice ☒ ☒ ☒ ☒

Minimum order 1 linear(s) meter(s)



Technical characteristics

Flame retardant

M1

Resilience

Lightfastness (units Class/8)

4

Dimensional Stability (%)

Warp

0

Weft

-0.5

Breaking Elongation

Warp

20

Weft

21

Breaking load (daN)

Warp

53

Weft

77



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected