



3141 bpi 00
Printing support



RUSTIC Prairie 125
Print pattern



Printing support 3141 bpi 00 Print pattern RUSTIC Prairie 125

Sheer fabric support for digital printing.

Technical properties



Flame retardant Transparent

Applications Roman blinds - Panel curtains - Curtains

Composition polyester/polyester FR

Weight 50 g/m²

Width 290 cm

Fabric direction Room High Direction

Fitting ↔ cm ↓ cm

Maintenance advice     

Label France Terre Textile / OEKO-TEX STANDARD 100

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Technical characteristics

Flame retardant	M1 / B1 / IMO PASS																				
Optical index	<table border="0"> <tr> <td>Light reflexion :</td> <td>25 %</td> </tr> <tr> <td>Light absorption :</td> <td>4 %</td> </tr> <tr> <td>Light transmission :</td> <td>71 %</td> </tr> </table>	Light reflexion :	25 %	Light absorption :	4 %	Light transmission :	71 %														
Light reflexion :	25 %																				
Light absorption :	4 %																				
Light transmission :	71 %																				
Transparent veil	Yes																				
Thermal index	<table border="0"> <tr> <td>Solar reflexion :</td> <td>25 %</td> </tr> <tr> <td>Solar absorption :</td> <td>3 %</td> </tr> <tr> <td>Solar transmission :</td> <td>72 %</td> </tr> <tr> <td>UV transmission :</td> <td>65 %</td> </tr> <tr> <td>Gtot :</td> <td>Gt 50 % Fc 85 %</td> </tr> </table>	Solar reflexion :	25 %	Solar absorption :	3 %	Solar transmission :	72 %	UV transmission :	65 %	Gtot :	Gt 50 % Fc 85 %										
Solar reflexion :	25 %																				
Solar absorption :	3 %																				
Solar transmission :	72 %																				
UV transmission :	65 %																				
Gtot :	Gt 50 % Fc 85 %																				
Resilience	<table border="0"> <tr> <td>Lightfastness (units Class/8)</td> <td>6</td> </tr> <tr> <td>Dimensional Stability (%)</td> <td></td> </tr> <tr> <td> Warp</td> <td>-1</td> </tr> <tr> <td> Weft</td> <td>0</td> </tr> <tr> <td>Breaking Elongation</td> <td></td> </tr> <tr> <td> Warp</td> <td>28</td> </tr> <tr> <td> Weft</td> <td>34</td> </tr> <tr> <td>Breaking load (daN)</td> <td></td> </tr> <tr> <td> Warp</td> <td>30</td> </tr> <tr> <td> Weft</td> <td>36</td> </tr> </table>	Lightfastness (units Class/8)	6	Dimensional Stability (%)		Warp	-1	Weft	0	Breaking Elongation		Warp	28	Weft	34	Breaking load (daN)		Warp	30	Weft	36
Lightfastness (units Class/8)	6																				
Dimensional Stability (%)																					
Warp	-1																				
Weft	0																				
Breaking Elongation																					
Warp	28																				
Weft	34																				
Breaking load (daN)																					
Warp	30																				
Weft	36																				

Print pattern RUSTIC



RUSTIC Lin 11



RUSTIC Naturel 26



RUSTIC Sienne 29



RUSTIC Terre 107



RUSTIC Taupe 95



RUSTIC Titanium 98



RUSTIC Hortensia 134



RUSTIC Bergamote 121



RUSTIC Mousse 92



RUSTIC Glacier 43



RUSTIC Bleu 41



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected