



**834S BLANC 01**  
Printing support



**LIV AUTOMNE 205**  
Print pattern

## Printing support **834S BLANC 01** Print pattern **LIV AUTOMNE 205**

Light and aerial gauze, the 834 S offers privacy meanwhile letting the light get through, its weaving technique gives it a great finesse and a good resistance.

### Technical properties



Flame retardant Transparent

**Applications** Roman blinds - Panel curtains - Curtains

**Composition** polyester/polyester FR

**Weight** 40 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 100.0 cm ↓ 300.0 cm

**Maintenance advice**    

**Label** France Terre Textile

**Minimum order** 1 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

|                  |                               |            |
|------------------|-------------------------------|------------|
| Flame retardant  | M1 / B1 / IMO PASS            |            |
| Transparent veil | Yes                           |            |
| Resilience       | Lightfastness (units Class/8) | <b>6</b>   |
|                  | Dimensional Stability (%)     |            |
|                  | Warp                          | <b>0.5</b> |
|                  | Weft                          | <b>0</b>   |
|                  | Breaking Elongation           |            |
|                  | Warp                          | <b>36</b>  |
|                  | Weft                          | <b>33</b>  |
|                  | Breaking load (daN)           |            |
|                  | Warp                          | <b>31</b>  |
|                  | Weft                          | <b>23</b>  |

# Print pattern LIV



LIV PRINTEMPS 130



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60  
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected