

# ASTRAL BPI 00

Blackout Print Support

## Technical properties



Thermal

Applications Roman blinds - Panel curtains - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 280 g/m<sup>2</sup> Width 280 cm

Fabric direction Room high or standard direction Fitting ↔ cm ↓ cm

Maintenance advice

Minimum order 25 linear(s) meter(s)

## Technical characteristics

Flame retardant

EN13773 : 2003 Class 1 / BS 5867 TYPE C / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno

Optical index

|                      |      |
|----------------------|------|
| Light reflexion :    | 82 % |
| Light absorption :   | 18 % |
| Light transmission : | 0 %  |

Thermal index

|                      |                 |
|----------------------|-----------------|
| Solar reflexion :    | 74 %            |
| Solar absorption :   | 26 %            |
| Solar transmission : | 0 %             |
| UV transmission :    | 0 %             |
| Gtot :               | Gt 33 % Fc 55 % |

Resilience

|                               |      |
|-------------------------------|------|
| Lightfastness (units Class/8) | 5    |
| Dimensional Stability (%)     |      |
| Warp                          | -0,5 |
| Weft                          | 0    |
| Breaking Elongation           |      |
| Warp                          | 26   |
| Weft                          | 15   |
| Breaking load (daN)           |      |
| Warp                          | 62   |
| Weft                          | 31   |



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60  
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on supports selected