



**BOREAL BPI 00**  
Printing support



**RUSTIC Prairie 125**  
Print pattern



## Printing support **BOREAL BPI 00** Print pattern **RUSTIC Prairie 125**

Dimout support for digital printing

### Technical properties



Flame retardant



Thermal



Acoustic

**Applications** Roman blinds - Valences - Lining - Bed runners - Curtains

**Composition** 100% FR polyester

**Weight** 260 g/m<sup>2</sup>

**Width** 145 cm

**Fabric direction** Standard Direction

**Fitting** ↔ cm ↓ cm

**Maintenance advice**     

**Label** OEKO-TEX STANDARD 100

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

|                 |   |
|-----------------|---|
| Flame retardant | M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno |
| Acoustic        | Noise reduction coefficient (NRC) : <b>0.88</b> |
| Resilience      | Dimensional Stability (%)                       |
|                 | Warp <b>0</b>                                   |
|                 | Weft <b>0</b>                                   |
|                 | Breaking Elongation                             |
|                 | Warp <b>17</b>                                  |
|                 | Weft <b>27</b>                                  |
|                 | Breaking load (daN)                             |
|                 | Warp <b>87</b>                                  |
|                 | Weft <b>110</b>                                 |

# Print pattern RUSTIC



RUSTIC Lin 11



RUSTIC Naturel 26



RUSTIC Sienne 29



RUSTIC Terre 107



RUSTIC Taupe 95



RUSTIC Titanium 98



RUSTIC Hortensia 134



RUSTIC Bergamote 121



RUSTIC Mousse 92



RUSTIC Glacier 43



RUSTIC Bleu 41



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60  
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected