




**BOREAL BPI 00**  
Printing support



**SAPHIR Reflet 140**  
Print pattern



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Printing support **BOREAL BPI 00** Print pattern **SAPHIR Reflet 140**

Dimout support for digital printing

### Technical properties



Flame retardant



Thermal



Acoustic

**Applications** Roman blinds - Valences - Lining - Bed runners - Curtains

**Composition** 100% FR polyester

**Weight** 260 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 0.0 cm ↓ 0.0 cm

**Maintenance advice**     

**Label** OEKO-TEX STANDARD 100

**Minimum order** 25 linear(s) meter(s)

## Technical characteristics

|                 |   |
|-----------------|---|
| Flame retardant | M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno |
| Acoustic        | Noise reduction coefficient (NRC) : <b>0.88</b> |
| Resilience      | Dimensional Stability (%)                       |
|                 | Warp <b>0</b>                                   |
|                 | Weft <b>0</b>                                   |
|                 | Breaking Elongation                             |
|                 | Warp <b>17</b>                                  |
|                 | Weft <b>27</b>                                  |
|                 | Breaking load (daN)                             |
|                 | Warp <b>87</b>                                  |
|                 | Weft <b>110</b>                                 |


# Print pattern SAPHIR




SAPHIR Naturel 26



SAPHIR Violine 105




SAPHIR Gentiane 16




SAPHIR Aubergine 27




SAPHIR Opéra 104



SAPHIR Absinthe 132



SAPHIR Hortensia 134



SAPHIR Acier 18



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

*Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected*