


BOREAL BPI 00
Printing support



SONG maïs 37
Print pattern

Printing support **BOREAL BPI 00** Print pattern **SONG maïs 37**

Dimout support for digital printing

Technical properties



Flame retardant



Thermal



Acoustic

Applications Roman blinds - Valences - Lining - Bed runners - Curtains

Composition 100% FR polyester

Weight 260 g/m²

Width 280 cm

Fabric direction Room High Direction

Fitting ↔ 35.0 cm ↓ 35.0 cm

Maintenance advice

Label OEKO-TEX STANDARD 100

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.


Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno
Acoustic	Noise reduction coefficient (NRC) : 0.88
Resilience	Dimensional Stability (%)
	Warp 0
	Weft 0
	Breaking Elongation
	Warp 17
	Weft 27
	Breaking load (daN)
	Warp 87
	Weft 110

Print pattern SONG



SONG Opéra 104




SONG Agrume 69




SONG Framboise 81




SONG Lierre 124




SONG Menthe 122




SONG Naturel 26




SONG Navy 120




SONG Océan 91




SONG Orage 123




SONG Orange 15




SONG Prairie 125



SONG Prune 84




SONG Sanguine 05




SONG Soleil 127



SONG Titanium 98




SONG Violine 105



SONG Jade 116



SONG Sapin 126



SONG Tilleul 103



sotexpro

(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected