

CORTE Mastic 48

This plain light-filtering fabric is available in several colours.

Technical properties



Flame retardant



Thermal

Applications Panel curtains - Bedspreads - Valences - Seating - Bed runners - Curtains - Cushions - Decorative frames - Roman blinds


Composition 100% FR polyester

Weight 230 g/m²

Width 140 cm / 280 cm

Fabric direction Room high or standard direction

Fitting ↔ cm ↓ cm

Maintenance advice     

Label OekoTex / France Terre Textile

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / BS 5867 TYPE C / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno
Acoustic	<p>Noise reduction coefficient (NRC) : 0.90</p> <p>Weighted sound absorption coefficient (a_w) : 0.85</p> <p>Acoustic absorption class (a_w) : B</p>
Optical index	<p>Light reflexion : 65 %</p> <p>Light absorption : 15 %</p> <p>Light transmission : 20 %</p>
Thermal index	<p>Solar reflexion : 63 %</p> <p>Solar absorption : 15 %</p> <p>Solar transmission : 22 %</p> <p>UV transmission : 3 %</p> <p>Gtot : Gt 37 % Fc 62 %</p>
Resilience	<p>Lightfastness (units Class/8) 5</p> <p>Dimensional Stability (%)</p> <p> Warp -2</p> <p> Weft -0.5</p> <p>Martindale (Cycles) 25000</p> <p>Breaking Elongation</p> <p> Warp 34</p> <p> Weft 28</p> <p>Breaking load (daN)</p> <p> Warp 130</p> <p> Weft 90</p>



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on supports selected