



LINOSA Tilleul 103

This plain, light-filtering fabric resembling linen is captivating and perfect for natural and warm décor.

Technical properties



Flame retardant

Applications Roman blinds - Panel curtains - Curtains - Cushions

Composition 100% FR polyester

Weight 260 g/m² Width 280 cm

Fabric direction Room High Direction Fitting ↔ cm ↓ cm

Maintenance advice

Labels France Terre Textile (R016)

Certifications OEKO-TEX STANDARD 100 (CQ 1006/1)

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno		
Optical index	Light reflexion :	59 %	
	Light absorption :	5 %	
	Light transmission :	36 %	
Thermal index	Solar reflexion :	58 %	
	Solar absorption :	7 %	
	Solar transmission :	35 %	
	UV transmission :	22 %	
	Gtot :	Gt 39 % Fc 65 %	
Resilience	Lightfastness (units Class/8)	6	
	Pilling	1-2	
	Dimensional Stability (%)	Warp	-2
		Weft	-0.5
	Martindale (Cycles)	30000	
	Breaking Elongation	Warp	25
		Weft	25
	Breaking load (daN)	Warp	140
		Weft	100



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on supports selected