



LY Blanc 01
Printing support



TERRA Graphite 77
Print pattern



Printing support **LY Blanc 01** Print pattern **TERRA Graphite 77**

Fine linen look sheer. The weaving of the LY is slightly textured which allows it to be easily printed by sublimation

Technical properties



Flame retardant Transparent

Applications Roman blinds - Panel curtains - Curtains

Composition 100% polyester/polyester FR

Weight 90 g/m²

Width 290 cm

Fabric direction Room High Direction

Fitting ↔ 0.0 cm ↓ 0.0 cm

Maintenance advice     

Label France Terre Textile / OEKO-TEX STANDARD 100

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Technical characteristics

Flame retardant	M1 / B1 / IMO PASS																				
Optical index	<table> <tr> <td>Light reflexion :</td> <td>33 %</td> </tr> <tr> <td>Light absorption :</td> <td>2 %</td> </tr> <tr> <td>Light transmission :</td> <td>65 %</td> </tr> </table>	Light reflexion :	33 %	Light absorption :	2 %	Light transmission :	65 %														
Light reflexion :	33 %																				
Light absorption :	2 %																				
Light transmission :	65 %																				
Transparent veil	Yes																				
Thermal index	<table> <tr> <td>Solar reflexion :</td> <td>32 %</td> </tr> <tr> <td>Solar absorption :</td> <td>4 %</td> </tr> <tr> <td>Solar transmission :</td> <td>64 %</td> </tr> <tr> <td>UV transmission :</td> <td>50 %</td> </tr> <tr> <td>Gtot :</td> <td>Gt 48 % Fc 81 %</td> </tr> </table>	Solar reflexion :	32 %	Solar absorption :	4 %	Solar transmission :	64 %	UV transmission :	50 %	Gtot :	Gt 48 % Fc 81 %										
Solar reflexion :	32 %																				
Solar absorption :	4 %																				
Solar transmission :	64 %																				
UV transmission :	50 %																				
Gtot :	Gt 48 % Fc 81 %																				
Resilience	<table> <tr> <td>Lightfastness (units Class/8)</td> <td>6</td> </tr> <tr> <td>Dimensional Stability (%)</td> <td></td> </tr> <tr> <td> Warp</td> <td>0</td> </tr> <tr> <td> Weft</td> <td>0</td> </tr> <tr> <td>Breaking Elongation</td> <td></td> </tr> <tr> <td> Warp</td> <td>69</td> </tr> <tr> <td> Weft</td> <td>58</td> </tr> <tr> <td>Breaking load (daN)</td> <td></td> </tr> <tr> <td> Warp</td> <td>47</td> </tr> <tr> <td> Weft</td> <td>24</td> </tr> </table>	Lightfastness (units Class/8)	6	Dimensional Stability (%)		Warp	0	Weft	0	Breaking Elongation		Warp	69	Weft	58	Breaking load (daN)		Warp	47	Weft	24
Lightfastness (units Class/8)	6																				
Dimensional Stability (%)																					
Warp	0																				
Weft	0																				
Breaking Elongation																					
Warp	69																				
Weft	58																				
Breaking load (daN)																					
Warp	47																				
Weft	24																				

Print pattern TERRA



TERRA Ficelle 09



TERRA Taupe 95



TERRA Ecume 82



TERRA Rose 129



TERRA Fusain 71



TERRA Brun 23



TERRA Hortensia 134



TERRA Naturel 26



TERRA Anis 62



TERRA Lagon 110



TERRA Citrouille 136



TERRA Pacifique 54



TERRA Chamois 111



TERRA Titanium 98



TERRA Gris 97



TERRA Ardoise 87



TERRA Violine 105



TERRA Chanvre 72



TERRA Argile 85



TERRA Lin 11



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected

Print pattern TERRA



TERRA Genêt 06



TERRA Céladon 135



TERRA Ebene 113



TERRA Ocre 03



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected