



# NATTE bpi 00

This light-filtering fabric serves as a print medium.

## Technical properties



Flame retardant

**Applications** Roman blinds - Panel curtains - Bedspreads - Valences - Bed runners - Curtains - Cushions

**Composition** 100% FR polyester

**Weight** 230 g/m<sup>2</sup> **Width** 280 cm

**Fabric direction** Room High Direction **Fitting** ↔ 0,0 cm ↓ 0,0 cm

**Maintenance advice**     

**Labels** France Terre Textile (R016)

**Certifications** OEKO-TEX STANDARD 100 (CQ 1006/1)

**Minimum order** 25 linear(s) meter(s)

## Technical characteristics

Flame retardant	M1 / IMO PASS		
Acoustic	Noise reduction coefficient (NRC) :	<b>0.90</b>	
Optical index	Light reflexion :	<b>5 %</b>	
	Light absorption :	<b>94 %</b>	
	Light transmission :	<b>1 %</b>	
Thermal index	Solar reflexion :	<b>39 %</b>	
	Solar absorption :	<b>48 %</b>	
	Solar transmission :	<b>13 %</b>	
	UV transmission :	<b>0 %</b>	
	Gtot :	<b>Gt 48 % Fc 69 %</b>	
Resilience	Lightfastness (units Class/8)	<b>5</b>	
	Pilling	<b>5</b>	
	Dimensional Stability (%)	Warp	<b>-2</b>
		Weft	<b>-1</b>
	Martindale (Cycles)	<b>40000</b>	
	Breaking Elongation	Warp	<b>38</b>
		Weft	<b>21</b>
	Breaking load (daN)	Warp	<b>150</b>
		Weft	<b>93</b>



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60  
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected