



NOCTIS BLANC Blanc 01

White blackout fabric.

Technical properties



Flame retardant

Applications Roman blinds - Roller blinds - Panel curtains - Lining - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 330 g/m² **Width** 200 cm

Fabric direction Room high or standard direction **Fitting** ↔ cm ↓ cm

Maintenance advice

Labels France Terre Textile (R016)

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno
Acoustic	Noise reduction coefficient (NRC) : 0.28
	Weighted sound absorption coefficient (a _w) : 0.20
	Acoustic absorption class (a _w) : E
Optical index	Light reflexion : 71 %
	Light absorption : 29 %
	Light transmission : 0 %
Thermal index	Solar reflexion : 66 %
	Solar absorption : 34 %
	Solar transmission : 0 %
	UV transmission : 0 %
	Gtot : Gt 35 % Fc 60 %
Resilience	Lightfastness (units Class/8) 6
	Pilling 5
	Dimensional Stability (%)
	Warp -0,5
	Weft 0
	Martindale (Cycles) 35000
	Breaking Elongation
	Warp 20
	Weft 24
	Breaking load (daN)
	Warp 53
Weft 63	



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on supports selected