NOCTURNE Tilleul 103

This blackout fabric is very efficient. It is available in a wide range of colors

Technical properties

Flame retardant Thermal

Applications Lining - Curtains - Roman blinds - Panel curtains

Composition 100% polyester with white flocked acrylic backing

Weight 280 g/m² **Width** 280 cm

Fabric direction Room high or standard direction **Fitting** ↔ cm ↕ cm

Maintenance advice

Minimum order 1 linear(s) metter(s)

Technical characteristics

Flame retardant	M1 / BS 5867 TYPE C / B1 / IMO PASS	
Optical index	Light reflexion :	**71 %**
	Light absorption :	**29 %**
	Light transmission :	**0 %**
Thermal index	Solar reflexion :	**66 %**
	Solar absorption :	**34 %**
	Solar transmission :	**0 %**
	UV transmission :	**0 %**
	Gtot :	**Gt 35 % Fc 60 %**
Resilience	Lightfastness (units Class/8)	**4**
	Pilling	**3-4**
	Dimentional Stability (%)	
	Warp	**-0,5**
	Weft	**0**
	Martindale (Cycles)	**40000**
	Breaking Elongation	
	Warp	**19**
	Weft	**22**
	Breaking load (daN)	
	Warp	**37**
	Weft	**57**

sotexpro

(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected