




**NOCTWIN BPI 00**  
Printing support



**SONG Tilleul 103**  
Print pattern



## Printing support **NOCTWIN BPI 00** Print pattern **SONG Tilleul 103**

Support occultant pour impression, imprimable des 2 côtés.

### Technical properties



Flame retardant

**Applications** Roman blinds - Panel curtains - Curtains

**Composition** Polyester/acrylique envers floqué

**Weight** 300 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 35.0 cm ↓ 35.0 cm

**Maintenance advice**     

**Label**

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

Flame retardant

B1 / IMO PASS

Resilience

Lightfastness (units Class/8)	6
Dimensional Stability (%)	
Warp	-1
Weft	0
Breaking Elongation	
Warp	31
Weft	8
Breaking load (daN)	
Warp	120
Weft	43

# Print pattern SONG



SONG Opéra 104



SONG Agrume 69



SONG Framboise 81




SONG Lierre 124



SONG Menthe 122



SONG Naturel 26



SONG Navy 120




SONG Océan 91



SONG Orage 123



SONG Orange 15




SONG Prairie 125



SONG Prune 84




SONG Sanguine 05




SONG Soleil 127



SONG Titanium 98




SONG Violine 105



SONG Jade 116



SONG Sapin 126



SONG maïs 37



sotexpro

(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60  
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected