



OPALE 2 Moutarde 21

This plain fabric blocks out light very effectively and is available in a wide variety of colours.

Technical properties



Flame retardant

Applications Roman blinds - Roller blinds - Panel curtains - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 290 g/m² 406 g/m² Width 140 cm

Fabric direction Standard Direction Fitting ↔ cm ↓ cm

Maintenance advice

Minimum order 1 linear(s) meter(s)

Technical characteristics

| | | |
|-----------------|-------------------------------|-----------------|
| Flame retardant | M1 / IMO PASS | |
| Optical index | Light reflexion : | 72 % |
| | Light absorption : | 28 % |
| | Light transmission : | 0 % |
| Thermal index | Solar reflexion : | 65 % |
| | Solar absorption : | 35 % |
| | Solar transmission : | 0 % |
| | UV transmission : | 0 % |
| | Gtot : | Gt 35 % Fc 60 % |
| Resilience | Lightfastness (units Class/8) | 5 |
| | Breaking Elongation | |
| | Warp | 35 |
| | Weft | 11 |



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected