



**OPAQ BPI 00**  
Printing support



**ELAINA Chamois 111**  
Print pattern



## Printing support **OPAQ BPI 00** Print pattern **ELAINA Chamois 111**

Unclassified blackout print support

### Technical properties

**Applications** Roman blinds - Panel curtains - Lining - Curtains

**Composition** 100% polyester with white flocked acrylic backing

**Weight** 280 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 0.0 cm ↑ 0.0 cm

**Maintenance advice**     

**Label**

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

|                     |                               |                        |
|---------------------|-------------------------------|------------------------|
| Optical index       | Light reflexion :             | <b>82 %</b>            |
|                     | Light absorption :            | <b>18 %</b>            |
|                     | Light transmission :          | <b>0 %</b>             |
| Thermal index       | Solar reflexion :             | <b>74 %</b>            |
|                     | Solar absorption :            | <b>26 %</b>            |
|                     | Solar transmission :          | <b>0 %</b>             |
|                     | UV transmission :             | <b>0 %</b>             |
|                     | Gtot :                        | <b>Gt 33 % Fc 55 %</b> |
| Resilience          | Lightfastness (units Class/8) | <b>5</b>               |
|                     | Dimensional Stability (%)     |                        |
|                     | Warp                          | <b>-0,5</b>            |
|                     | Weft                          | <b>0</b>               |
|                     | Breaking Elongation           |                        |
|                     | Warp                          | <b>26</b>              |
|                     | Weft                          | <b>15</b>              |
| Breaking load (daN) |                               |                        |
| Warp                | <b>62</b>                     |                        |
| Weft                | <b>31</b>                     |                        |

# Print pattern ELAINA



ELAINA Gris 91



ELAINA Violine 105



ELAINA Ocre 03



ELAINA Lin 11



ELAINA Bergamote 121



ELAINA Rose 129



ELAINA Pacifique 54



ELAINA Beige 63



ELAINA Céladon 135



ELAINA Saphir 106



ELAINA Anis 62



ELAINA Rouge 21



ELAINA Hortensia 134



ELAINA Prairie 125



ELAINA Graphite 77



ELAINA Lierre 124



ELAINA Naturel 26



ELAINA Genêt 06



ELAINA Ivoire 115



ELAINA Gentiane 16



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60  
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected



## Print pattern ELAINA



ELAINA Navy 120



ELAINA Turquoise 53



ELAINA Anthracite 38



ELAINA Fiesta 131



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60  
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

*Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected*