



**OPAQ BPI 00**  
Printing support



**TUMULTE Safran 49**  
Print pattern



## Printing support **OPAQ BPI 00** Print pattern **TUMULTE Safran 49**

Unclassified blackout print support

### Technical properties

**Applications** Roman blinds - Panel curtains - Lining - Curtains

**Composition** 100% polyester with white flocked acrylic backing

**Weight** 280 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 17.0 cm ↓ 15.0 cm

**Maintenance advice**     

**Label**

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

|                     |                               |                        |
|---------------------|-------------------------------|------------------------|
| Optical index       | Light reflexion :             | <b>82 %</b>            |
|                     | Light absorption :            | <b>18 %</b>            |
|                     | Light transmission :          | <b>0 %</b>             |
| Thermal index       | Solar reflexion :             | <b>74 %</b>            |
|                     | Solar absorption :            | <b>26 %</b>            |
|                     | Solar transmission :          | <b>0 %</b>             |
|                     | UV transmission :             | <b>0 %</b>             |
|                     | Gtot :                        | <b>Gt 33 % Fc 55 %</b> |
| Resilience          | Lightfastness (units Class/8) | <b>5</b>               |
|                     | Dimensional Stability (%)     |                        |
|                     | Warp                          | <b>-0,5</b>            |
|                     | Weft                          | <b>0</b>               |
|                     | Breaking Elongation           |                        |
|                     | Warp                          | <b>26</b>              |
|                     | Weft                          | <b>15</b>              |
| Breaking load (daN) |                               |                        |
| Warp                | <b>62</b>                     |                        |
| Weft                | <b>31</b>                     |                        |

## Print pattern TUMULTE



TUMULTE Lilas 19



TUMULTE Maïs 37



TUMULTE Orage 123



TUMULTE Prairie 125



TUMULTE Menthe 122



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60  
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected