




OPAQ BPI 00
Printing support



SONG Prairie 125
Print pattern



Printing support **OPAQ BPI 00** Print pattern **SONG Prairie 125**

Unclassified blackout print support

Technical properties

Applications Roman blinds - Panel curtains - Lining - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 280 g/m²

Width 280 cm

Fabric direction Room High Direction

Fitting ↔ 35.0 cm ↓ 35.0 cm

Maintenance advice     

Label

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Technical characteristics

Optical index

| | |
|----------------------|-------------|
| Light reflexion : | 82 % |
| Light absorption : | 18 % |
| Light transmission : | 0 % |

Thermal index

| | |
|----------------------|------------------------|
| Solar reflexion : | 74 % |
| Solar absorption : | 26 % |
| Solar transmission : | 0 % |
| UV transmission : | 0 % |
| Gtot : | Gt 33 % Fc 55 % |

Resilience

| | |
|-------------------------------|-------------|
| Lightfastness (units Class/8) | 5 |
| Dimensional Stability (%) | |
| Warp | -0,5 |
| Weft | 0 |
| Breaking Elongation | |
| Warp | 26 |
| Weft | 15 |
| Breaking load (daN) | |
| Warp | 62 |
| Weft | 31 |

Print pattern SONG



SONG Opéra 104



SONG Agrume 69



SONG Framboise 81



SONG Lierre 124



SONG Menthe 122



SONG Naturel 26



SONG Navy 120



SONG Océan 91



SONG Orage 123



SONG Orange 15



SONG Prune 84



SONG Sanguine 05



SONG Soleil 127



SONG Titanium 98



SONG Violine 105



SONG Jade 116



SONG Sapin 126



SONG Tilleul 103



SONG maïs 37



sotexpro

(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected