



SIENTO LITO Hortensia 134

Light-filtering fabric made from recycled yarns

Technical properties



Flame retardant



Recycled fabrics

Applications Roman blinds - Panel curtains - Curtains - Decorative frames

Composition 80% recycled polyester FR / 20% polyester FR

Weight 330 g/m² Width 290 cm

Fabric direction Room High Direction Fitting ↔ cm ↓ cm

Maintenance advice

Labels France Terre Textile (R016)

Certifications OEKO-TEX STANDARD 100 Recyclé (CQ 1006/2)

Minimum order 1 linear(s) meter(s)

Technical characteristics

| | |
|-----------------|---|
| Flame retardant | M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno |
| Acoustic | Noise reduction coefficient (NRC) : 0.76 |
| | Weighted sound absorption coefficient (a _w) : 0.70 |
| | Acoustic absorption class (a _w) : C |
| Optical index | Light reflexion : 48 % |
| | Light absorption : 41 % |
| | Light transmission : 11 % |
| Thermal index | Solar reflexion : 55 % |
| | Solar absorption : 25 % |
| | Solar transmission : 20 % |
| | UV transmission : 2 % |
| | Gtot : Gt 39 % Fc 67 % |
| | |
| Resilience | Lightfastness (units Class/8) 5 |
| | Pilling 1 |
| | Dimensional Stability (%) |
| | Warp -1 |
| | Weft -0.5 |
| | Martindale (Cycles) 20000 |
| | Breaking Elongation |
| | Warp 49 |
| | Weft 34 |
| | Breaking load (daN) |
| | Warp 140 |
| | Weft 79 |



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on supports selected