



SIENTO LITO Minéral 157

Light-filtering fabric made from recycled yarns

Technical properties



Flame retardant





Recycled fabrics

Applications Roman blinds - Panel curtains - Curtains - Decorative frames

Composition 80% recycled polyester FR / 20% polyester FR

Weight 330 g/m² **Width** 290 cm

Fabric direction Room High Direction **Fitting** ↔ cm ↓ cm

Maintenance advice     

Labels France Terre Textile (R016)

Certifications OEKO-TEX STANDARD 100 Recyclé (CQ 1006/2)

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno
Acoustic	Noise reduction coefficient (NRC) : 0.76
	Weighted sound absorption coefficient (a _w) : 0.70
	Acoustic absorption class (a _w) : C
Optical index	Light reflexion : 25 %
	Light absorption : 71 %
	Light transmission : 4 %
Thermal index	Solar reflexion : 41 %
	Solar absorption : 45 %
	Solar transmission : 14 %
	UV transmission : 2 %
	Gtot : Gt 44 % Fc 74 %
Resilience	Lightfastness (units Class/8) 5
	Pilling 1
	Dimensional Stability (%)
	Warp -1
	Weft -0.5
	Martindale (Cycles) 20000
	Breaking Elongation
	Warp 49
	Weft 34
	Breaking load (daN)
	Warp 140
	Weft 79



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on supports selected