



**SIENTO RECYCLE UNI Lin 11**  
Printing support



**6058 Kaki 148**  
Print pattern

## Printing support **SIENTO RECYCLE** **UNI Lin 11** Print pattern **6058 Kaki 148**

Heavy canvas fabric, the Siento recyclé is woven with mixed dyed yarns which gives this textured linen effect. The warp and weft are made with recycled polyester yarns. Usable as a printing support. Please note : the background can modify the coloristic rendering.

### Technical properties



Flame retardant



Thermal



Acoustic



Recycled fabrics

**Applications** Roman blinds - Panel curtains - Bedspreads - Valences - Seating - Bed runners - Curtains - Cushions

**Composition** 80% recycled polyester FR / 20% polyester FR

**Weight** 330 g/m<sup>2</sup>

**Width** 290 cm

**Fabric direction** Room high or standard direction

**Fitting** → 25.0 cm ↓ 25.0 cm

**Maintenance advice**

**Label** France Terre Textile / OEKO-TEX STANDARD 100 Recyclé

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno
Acoustic	Noise reduction coefficient (NRC) : <b>0.73</b>
Optical index	Light reflexion : <b>41 %</b>
	Light absorption : <b>51 %</b>
	Light transmission : <b>8 %</b>
Thermal index	Solar reflexion : <b>55 %</b>
	Solar absorption : <b>29 %</b>
	Solar transmission : <b>16 %</b>
	UV transmission : <b>5 %</b>
	Gtot : <b>Gt 39 % Fc 66 %</b>
Resilience	Lightfastness (units Class/8) <b>6</b>
	Pilling <b>4-5</b>
	Dimensional Stability (%)
	Warp <b>-1,5</b>
	Weft <b>-1,5</b>
	Martindale (Cycles) <b>90000</b>
	Breaking Elongation
	Warp <b>41</b>
	Weft <b>44</b>
	Breaking load (daN)
Warp <b>180</b>	
Weft <b>150</b>	