

SIENTO RECYCLE UNI Lin 11
Printing support



ANGELE Vert 24
Print pattern

Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Printing support **SIENTO RECYCLE UNI Lin 11**
Print pattern **ANGELE Vert 24**

Heavy canvas fabric, the Siento recyclé is woven with mixed dyed yarns which gives this textured linen effect. The warp and weft are made with recycled polyester yarns. Usable as a printing support. Please note : the background can modify the coloristic rendering. NOT USED printed fabric on seat

Technical properties

Flame retardant · Thermal · Acoustic · Recycled fabrics

Applications Roman blinds - Panel curtains - Bedspreads - Valences - Seating - Bed runners - Curtains - Cushions

Composition 100% FR polyester including 95% recycled material

Weight 370 g/m²

Width 280 cm

Fabric direction Room high or standard direction

Fitting ↔ 30.0 cm ↕ 30.0 cm

Maintenance advice

Label France Terre Textile / OEKO-TEX STANDARD 100 Recyclé

Minimum order 25 linear(s) metter(s)

Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno	
Acoustic	Noise reduction coefficient (NRC) :	**0.73**
Optical index	Light reflexion :	**41 %**
	Light absorption :	**51 %**
	Light transmission :	**8 %**
Thermal index	Solar reflexion :	**55 %**
	Solar absorption :	**29 %**
	Solar transmission :	**16 %**
	UV transmission :	**5 %**
	Gtot :	**Gt 39 % Fc 66 %**
Resilience	Lightfastness (units Class/8)	**6**
	Pilling	**4-5**
	Dimentional Stability (%)	
	Warp	**-1,5**
	Weft	**-1,5**
	Martindale (Cycles)	**90000**
	Breaking Elongation	
	Warp	**41**
	Weft	**44**
	Breaking load (daN)	
	Warp	**180**
	Weft	**150**

Print pattern ANGELE


ANGELE Océan 91


ANGELE Taupe 95

ANGELE Anis 62


ANGELE Fuchsia 33


ANGELE Orange 15

ANGELE Prune 84


ANGELE Sable 67


ANGELE Turquoise 53

sotexpro

(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected