



SIENTO RECYCLE UNI Lin 11
Printing support



6049 Naturel 26
Print pattern

Printing support **SIENTO RECYCLE** **UNI Lin 11** Print pattern **6049 Naturel 26**

Heavy canvas fabric, the Siento recyclé is woven with mixed dyed yarns which gives this textured linen effect. The warp and weft are made with recycled polyester yarns. Usable as a printing support. Please note : the background can modify the coloristic rendering.

Technical properties



Flame retardant



Thermal



Acoustic



Recycled fabrics

Applications Roman blinds - Panel curtains - Bedspreads - Valences - Seating - Bed runners - Curtains - Cushions

Composition 80% recycled polyester FR / 20% polyester FR

Weight 330 g/m²

Width 290 cm

Fabric direction Room high or standard direction

Fitting ↔ 32.0 cm ↓ 32.0 cm

Maintenance advice

Label France Terre Textile / OEKO-TEX STANDARD 100 Recyclé

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Technical characteristics

| | |
|-----------------|---|
| Flame retardant | M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno |
| Acoustic | Noise reduction coefficient (NRC) : 0.73 |
| Optical index | Light reflexion : 41 % |
| | Light absorption : 51 % |
| | Light transmission : 8 % |
| Thermal index | Solar reflexion : 55 % |
| | Solar absorption : 29 % |
| | Solar transmission : 16 % |
| | UV transmission : 5 % |
| | Gtot : Gt 39 % Fc 66 % |
| | Resilience |
| | Pilling 4-5 |
| | Dimensional Stability (%) |
| | Warp -1,5 |
| | Weft -1,5 |
| | Martindale (Cycles) 90000 |
| | Breaking Elongation |
| | Warp 41 |
| | Weft 44 |
| | Breaking load (daN) |
| | Warp 180 |
| | Weft 150 |