



SOFTLINE Blanc 01  
Printing support



VIBRATO Vert 24  
Print pattern



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Printing support **SOFTLINE Blanc 01** Print pattern **VIBRATO Vert 24**

Light and soft canvas with peach skin touch, ideal for slightly filtering light into a room. The Softline can also be used as a lining to provide an extra finishing to your double-lined curtains.

### Technical properties



Flame retardant



Thermal

Applications Roman blinds - Panel curtains - Lining - Curtains

Composition 100% FR polyester

Weight 80 g/m<sup>2</sup>

Width 300 cm

Fabric direction Room high or standard direction

Fitting → 8.0 cm ↓ 0.0 cm

Maintenance advice      

Label

Minimum order 25 linear(s) meter(s)

## Technical characteristics

|                 |                               |                 |
|-----------------|-------------------------------|-----------------|
| Flame retardant | M1 / B1 / IMO PASS            |                 |
| Optical index   | Light reflexion :             | 63 %            |
|                 | Light absorption :            | 5 %             |
|                 | Light transmission :          | 32 %            |
| Thermal index   | Solar reflexion :             | 63 %            |
|                 | Solar absorption :            | 5 %             |
|                 | Solar transmission :          | 32 %            |
|                 | UV transmission :             | 25 %            |
|                 | Gtot :                        | Gt 37 % Fc 62 % |
| Resilience      | Lightfastness (units Class/8) | 6               |
|                 | Dimensional Stability (%)     |                 |
|                 | Warp                          | -0.5            |
|                 | Weft                          | -0.5            |
|                 | Breaking Elongation           |                 |
|                 | Warp                          | 25              |
|                 | Weft                          | 10              |
|                 | Breaking load (daN)           |                 |
| Warp            | 45                            |                 |
| Weft            | 23                            |                 |