

SOFTLINE Champagne 02

Light and soft canvas with peach skin touch, ideal for slightly filtering light into a room. The Softline can also be used as a lining to provide an extra finishing to your double-lined curtains.

Technical properties



Flame retardant






Thermal

Applications Roman blinds - Panel curtains - Lining - Curtains

Composition 100% FR polyester

Weight 80 g/m² **Width** 290 cm

Fabric direction Room high or standard direction **Fitting** ↔ cm ↓ cm

Maintenance advice     

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / B1 / IMO PASS
Optical index	Light reflexion : 63 %
	Light absorption : 5 %
	Light transmission : 32 %
Thermal index	Solar reflexion : 63 %
	Solar absorption : 5 %
	Solar transmission : 32 %
	UV transmission : 25 %
	Gtot : Gt 37 % Fc 62 %
Resilience	Lightfastness (units Class/8) 6
	Dimensional Stability (%)
	Warp -0.5
	Weft -0.5
	Breaking Elongation
	Warp 25
	Weft 10
	Breaking load (daN)
	Warp 45
Weft 23	



(Headquarters) SOTEXPRO - 510 route de Montchal - 42360 PANISSIÈRES - FRANCE - +33 4 77 27 60 60
(Showroom) Le LAB' SOTEXPRO - 4 rue du Mail - 75002 PARIS - FRANCE

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on supports selected